UNIVERSAL DEFROST TIMER

9145-9045 SERIES - MULTI-VOLTAGE 120/208-240 VAC



GENERAL INFORMATION

Input power

120/208-240 VAC 60 Hz (+10, -15%)

Power consumption

6VA max, Defrost termination switch (terminal "G") input impedance

to terminal C: $85k\Omega + -5\%$

Operating voltage

102 VAC min to 132 VAC max @ 60 Hz

176.8 VAC min to 264 VAC max @ 60Hz

NOTE: No user-required adjustments to switch between the high and low voltage.

Ambient operating conditions

-40°F to 131°F (-40°C to 55°C); 0 to 95% RH (non condensing)

Storage temperature

-40°F to 140°F (-40°C to 60°C)

Outside dimensions

Individual unit 4.40"W x 7.82"H x 3.80"D

Individual unit (in shipping box)

4.75"W x 8.875"H x 4.75"D

Individual case shipping weight

3.2 lbs

Agency approvals

c-UR-us Recognized Component - Models 9045-00M & 9145-00M

c-UR-us Listed Product - Models 9045-00 & 9145-00

Terminal	Α	В	С	D	E	F	G
Relay	SPDT	SPDT	SPDT	SPST	SPST	L2/N	Defrost Termination
Contact	NC Contact	NO Contact	COMM Contact	NO Contact	COMM Contact	Power in to timer	Device Input
							L2/N side
Relay	15A resistive @	30A resistive @			30A resistive @		
Rating	120 VAC to 240 VAC	120 VAC to 240 VAC			120 VAC to 240 VAC		
	1/4HP @ 120 VAC, 1/2HP @ 208 VAC	1HP @ 120 VAC, 2HP @ 208 VAC			1HP @ 120 VAC, 2HP @ 208 VAC		
	to 240 VAC	to 240 VAC			to 240 VAC		
Device	Fan (Typical)	Defrost Device	L1 Power to timer		Compressor		Defrost
Connections	Compressor	(Typical)	and to Defrost		(Typical)		Termination
	(Optional)		Termination Device		Fan (Optional)		Switch

 $^{*\,9145\,\}text{is a general purpose defrost timer}\,\&\,\text{can be used for both Time Initiate/Time Terminate}\,\&\,\text{Time Initiate/Temperature, Pressure Terminate}$

Terminal	Α	В	С	D	E	F	G
Relay	SPST#1	SPST#1	L1	SPST#2	SPST#2	L2/N	No Connection
Contact	NC Contact	COMM Contact	Power in to timer	NO Contact	COMM Contact	Power in to timer	
Relay Rating	30A resistive @ 120VAC to 240 VAC 1HP @ 120 VAC, 2HP @208 VAC to 240VAC				30A resistive @ 120 VAC to 240 VAC 1HP @ 120 VAC, 2HP @208 VAC to 240 VAC		
Device Connections	Compressor (Typical)				Defrost Device (Typical)		

Ordering Information: 9145-00 Time Initiate/Temperature, Pressure Terminate Defrost Timer with Metal Enclosure 9045-00 Time Initiate/Time Terminate Defrost Timer with Metal Enclosure