# **P77**

## Single Pressure for IP54 Applications

The P77 series pressure controls may be used for control functions or limit functions, depending on model number.

All models are provided with alarm contacts. All standard models have phosphor bronze bellows and brass pressure connections.

Models for use with ammonia are provided with stainless steel bellows and connectors.

Devices conforming to PED 97/23/EC Cat. IV (HP models) have the fail-safe function with double bellows.

Their IP54 classification means that these pressure controls are suitable for almost all applications.

#### **Features**


- Generous wiring space
- Splash-proof enclosure (IP54)
- SPDT contacts are provided as standard on single pressure controls.
- Trip-free manual reset

#### **Application**

These pressure controls are designed for use in a variety of applications involving refrigeration high or low pressure.

Models supplied have a "whole range" design, enabling them to be used with refrigerants R22, R134A, R404A, R410A and all other non-corrosive refrigerants which are within the operating range of the control. They may also be used for other high or low pressure applications such as air, water etc. Models which can be used with ammonia are included in the program. Also models tested and approved to PED 97/23/EC Cat. IV (supersedes DIN and TUV approval) are included in the program.





Dimensions in mm



Style 5



Style 15

Style 28







#### **REFRIGERATION COMPONENTS**

**Pressure Controls** 

252

## P77

# Single Pressure for IP54 Applications

Ordering Codes	Range (bar)	Differential (bar)	Wiring/ Action	Style	Pack.	Refr.	Additional Features	PED Approval
P77AAA-9300	-0.5 to 7	0.5 to 3	1	5	ind.	non-corr.		
P77AAA-9301	-0.2 to 10	1 to 4.5						
P77AAA-9302	-0.3 to 2	0.4 to 1.5						
P77AAA-9320*	-0.5 to 7	0.5 to 3			bulk		Is P77AAA-9300 bulk pack	
P77AAA-9350	3 to 30	3 to 12	2		ind.			
P77AAA-9351	3.5 to 21	2 to 5.5						
P77AAA-9370*	3 to 30	3 to 12			bulk		Is P77AAA-9350 bulk pack	
P77AAA-9371*	3.5 to 21	2 to 5.5					Is P77AAA-9351 bulk pack	
P77AAA-9400	-0.5 to 7	0.5 to 3	1	30	ind.		P77AAA-9300 solder connection ¼ "ODF	
P77AAA-9450	3 to 30	3 to 12	2				P77AAA-9350 solder connection 1/4 "ODF	
P77AAA-9451	3.5 to 21	2 to 5.5					P77AAA-9351 solder connection ¼ "ODF	
P77AAA-9700	-0.5 to 7	0.5 to 3		15		NH3		
P77AAA-9750	3 to 30	3 to 12						
P77AAA-9800	-0.5 to 7	0.5 to 3	1 2	28	ind.	non-corr.	P77AAA-9300 solder connection 6 mm ODM	
P77AAA-9850	3 to 30	3 to 12					P77AAA-9350 solder connection 6 mm ODM	

#### Notes



<sup>\* :</sup> Quantity orders only

P77
Single Pressure for IP54 Applications

Ordering Codes	Range (bar)	Diff. (bar)	Wiring/ Action	Style	Pack.	Refr.	Additional Features	PED Approval				
P77 Pressure Controls Automatic Recycle (Wächter, including lockplate assy)												
P77AAW-9300	-0.5 to +7	0.5 to 3				non-corr.						
P77AAW-9301*	-0.5 to +7	0.5 to 3	1		ind.		Gold plated contacts; Fixed setting: Open:0,5 bar; Close: 1,25 bar					
P77AAW-9320*	-0.5 to +7	0.5 to 3	]		bulk		P77AAW-9300 in bulk pack					
P77AAW-9350	3 to 30	3.5 to 12			ind.			•				
P77AAW-9353*	3 to 30	3.5 to 12	2				Gold plated contacts; Fixed setting: Open 7 bar; Close: 11 bar					
P77AAW-9355	3 to 42	4 to 12		5	ind.							
P77AAW-9370*	3 to 30	3.5 to 12			bulk		P77AAW-9350 in bulk pack					
P77AAW-9700	-0.5 to +7	0.5 to 3	1	15		NH3						
P77AAW-9750	3 to 30	3.5 to 12	2	15				•				
P77AAW-9800	-0.5 to +7	0.5 to 3	1	1	ind. 28		P77AAW-9300 solder connection - 6 mm ODM					
P77AAW-9850	3 to 30	3.5 to 12				non-corr.	P77AAW-9350 solder connection - 6 mm ODM	•				
P77AAW-9851*	3 to 30	3.5 to 12	2	28			Gold plated contacts; Fixed setting: Open 7 bar; Close: 11 bar, with solder connection 6 mm ODM					
P77AAW-9855	3 to 42	4 to 12	2									
	,	1	P7	7 Pressu	re Cont	rols Manu	al Reset LP					
P77BCA-9300			1	5	ind.	non-corr.  NH3						
P77BCA-9400				30			P77BCA-9300 solder connection ¼ " ODF					
P77BCA-9700	-0.5 to +7			15								
P77BCB-9300	_			5								
P77BCB-9800			28		ind.		P77BCB -9300 solder connection - 6 mm ODM					
	1		P7	7 Pressu	re Cont	rols Manu	al Reset HP					
P77BEA-9350				5	ind.	non-corr.						
P77BEA-9450	3 to 30		3	30	ind.		P77BEA-9350 solder connection ¼ " ODF					
P77BEA-9750						NH3						
	1	P7	7 Pressure	Contro	ls (Begr	enzer, incl	uding lockplate assy)	1				
P77BEB-9350	3 to 30				ind.							
P77BEB-9355	3 to 42		5		non-corr.		_					
P77BEB-9370*			3		bulk		P77BEB-9350 in bulk pack	•				
P77BEB-9750	3 to 30			15		NH3						
P77BEB-9850	_			28	ind.	non-corr.	P77BEB-9350 solder connection - 6 mm ODM					
P77BEB-9855	3 to 42			(6: :								
	F	777 Pressu	re Control	s (Siche	1	uckbegrer	zer, including lockplate assy)	T				
P77BES-9350	3 to 30		5	ind.	non-corr.							
P77BES-9370			3	4-	bulk 	NII 10	 	•				
P77BES-9750				15	ind.	NH3						
P77BES-9850				28	ind.	non-corr.	P77BES-9350 solder connection - 6 mm ODM					

Note



### THE EUROPEAN PRODUCTS CATALOGUE 2011

<sup>\* :</sup> Quantity orders only